

# Eaton 266685

Catalog Number: 266685

Eaton Moeller series NZM - Molded Case Circuit Breaker. Remote operator, 208-240VAC, for size 4



Photo is representative

## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Eaton Moeller series NZM remote operator	266685
	<b>Model Code</b>
	NZM4-XR208-240AC
<b>EAN</b>	<b>Product Length/Depth</b>
4015082666859	189 mm
<b>Product Height</b>	<b>Product Width</b>
202 mm	210 mm
<b>Product Weight</b>	<b>Compliances</b>
6.1 kg	IEC
	UL/CSA
	RoHS conform

## Certifications

CSA certified  
CSA (Class No. 1437-01)  
UL listed  
UL489  
UL (File No. E140305)  
UL (Category Control Number DIHS)  
CE marking  
IEC60947  
CSA (File No. 22086)  
CSA-C22.2 No. 5-09

## Product specifications

### Used with

N(S)4(-4)

NZM4(-4)

### Type

Accessory

Remote operator, can be synchronized

### Special features

Cannot be combined with switch-disconnector PN...

Do not install M22-

CK11(20/02) dual auxiliary

contacts in the right-hand

side auxiliary contact slot in

NZM4-XR

### Voltage rating

208 - 240 V 50/60 Hz

#### 10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

#### 10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

#### 10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

#### 10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

#### 10.2.2 Corrosion resistance

Meets the product standard's requirements.

##### 10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

##### 10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

##### 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal

## Resources

### Brochures

[eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf](#)

[eaton-digital-nzm-brochure-br013003en-en-us.pdf](#)

### Catalogs

[eaton-digital-nzm-catalog-ca013003en-en-us.pdf](#)

### Declarations of conformity

[DA-DC-03\\_NZM4](#)

### Drawings

[eaton-circuit-breaker-remote-operator-nzm-remote-operator-dimensions-003.eps](#)

[123X196](#)

[123X465](#)

[eaton-circuit-breaker-padlock-nzm-rotary-handle-dimensions.eps](#)

### eCAD model

[ETN.NZM4-XR208-240AC](#)

[ETN.266685.edz](#)

### Installation instructions

[eaton-nzm4-remote-operator-xr-il01210006z.pdf](#)

### Installation videos

[The new digital NZM Range](#)

[Introduction of the new digital circuit breaker NZM](#)

### mCAD model

[eaton-cadenas-side\\_view-nzm4\\_xr\\_side.pra](#)

[eaton-cadenas-path-circuit\\_breaker-nzm4\\_xr.3db](#)

[DA-CD-nzm4\\_xr](#)

[DA-CS-nzm4\\_xr](#)

[eaton-cadenas-front\\_view-nzm4\\_xr\\_front.pra](#)

### Technical data sheets

[eaton-nzm-technical-information-sheet](#)

elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

Frame

NZM4

Breaking time

3000 ms

Closing delay

100 ms

Voltage type

AC

Lifespan, mechanical

10000 operations

Number of poles

Three-pole/Four-pole

Number of operations per hour - max

20

Voltage tolerance - max

1.1

Voltage tolerance - min

.85

Rated control supply voltage (Us) at AC, 50 Hz - max

240 V

Rated control supply voltage (Us) at AC, 50 Hz - min

208 V

Rated control supply voltage (Us) at AC, 60 Hz - max

240 V

Rated control supply voltage (Us) at AC, 60 Hz - min

208 V

Rated control supply voltage (Us) at DC - max

0 V

Rated control supply voltage (Us) at DC - min

0 V

Rated operating frequency

50 Hz

Signal duration of remote operator at switch off - min

500 ms

Signal duration of remote operator at switch on - min

30 ms

Switch drive type

Motor drive

Terminal capacity (solid/flexible conductor)

0.75 mm<sup>2</sup> - 2.5 mm<sup>2</sup> with ferrule

18 - 14 AWG

Operating voltage - max

1.1 x Us

Operating voltage - min

0.85 x Us

Power consumption

350 VA (110 - 130 V AC)



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)